

ACCESSORIES

MANUAL SPRAY PUMP PROTEC HSP3K

WITH METAL CONTAINER

PROPERTIES

- Metal container is resistant to temperatures
- Metal nozzle for perfect spray pattern, easy to handle
- Pump produced without foreign matter, no silicone guaranteed
- Ideal to apply PROTEC CE15L+, CE16M and LC20A anti-spatter fluids
- Dedicated variant for PROTEC CE15V+ (with larger nozzle)

APPLICATION

- Enables easy filling, we recommend using a drain valve for the canister
- Upon first use, fully close the valve to the limit stop, then open by approximately one turn and pump until fluid has been sucked in.
- Set valve to desired spray pattern (usually opened by approximately 1/2 turn).
- Evenly spray work-pieces from a distance of approximately 30cm.

Note: one stroke with the pump enables to coat a larger area. Set the pressure accordingly during pumping. Forcefully pressing the pump lever damages the pump (hydraulic pressure).

SPECIFICATIONS

- Metal container, capacity 500ml
- Plastic pump with brass nozzle to achieve an acute spray pattern

Item

- **Manual spray pump PROTEC HSP3K:** ID no. **Z003.001**
- **Manual spray pump PROTEC HSP3K-V,** especially for PROTEC CE15V+ (with larger nozzle): ID no. **Z003.002**