



CCG 18-125-10 AS

Cordless angle grinder, 125 mm in diameter

Dust-resistant and powerful, compact cordless angle grinder for effective cutting, grinding and deburring work in assembly jobs.

Product number: 7 122 02 61 00 0



Details

- Guarantees very long life with the next generation of brushless FEIN PowerDrive motors. Totally closed motor housing protects the motor from aggressive ceramic and mineral dusts.
- Ideal for every application. Optimum speeds, matched to a large number of abrasive materials and other materials using the infinitely variable, electronic speed preselection.
- + Powerful. 30% more efficiency than comparable universal motors with a rated output of 1080 W.
- → Delivers the same power as an equivalent corded 1080 W angle grinder.
- Maintenance-free motor with innovative cooling ribs for optimum heat dissipation, including monitoring of temperature.
- + COOLPACK 2.0 technology delivers a 135% longer battery life and therefore makes longer operating times possible.
- + State-of-the-art cell technology and intelligent battery management deliver 87% more power than with conventional batteries.
- + ProCORE Li-Ion battery with high-power cells, charge status indicator and "Electronic Cell

- Protection" (ECP). ECP protects against overload, overheating and total discharge.
- Very smooth running and low-vibration working thanks to motor being decoupled from the housing and mounted separately and four additional vibration dampers.
- + Extensive user protection features include soft start, restart protection, electronic overload protection and brake.
- + Fatigue-free working thanks to narrow grip dimensions, compact design and a well-balanced low weight.
- + Separate motor electronics with dust guard in handle area.
- + Compatible with all 18 V AMPShare ProCORE batteries and chargers for even more power and flexibility. Also suitable for 18 V Bosch Professional cordless devices.
- → Safety hood, which can be adjusted without the use of tools, and quick-clamping nuts make for short setup times.
- Bright working area thanks to integrated LED light.
- → Ideally equipped for every form of use. Mobile working with the L-BOXX system.

Price includes

- + 1 wheel guard
- + 1 anti-vibration handle
- + 1 plastic tool case (L-BOXX 238)
- + 1 Tool-free quick-clamping nut
- + 1 key

Product feature

- + Brake
- + Soft start
- Blockage monitoring
- + Electronic speed preselection
- + POWERtronic tacho electronics
- + Restart protection
- + Electronic overload protection



Application

Roughing-down

Deburring

Dividing

Brushing

Satin-finishing

Technical data

TECHNICAL DATA

Battery voltage 18 V Li-ion / ProCORE Li-ion Battery compatibility Battery interface 18 V AMPShare Motor brushless 2,500 - 8,500 rpm Speed, no load Grinding disc Ø 125 mm 125 mm Elast. Backing pad Ø M 14 Flange Weight without storage 2.00 kg battery



VIBRATION AND SOUND EMISSION VALUES

Sound pressure level LpA 86 dB

Uncertainty of measured value KpA	3 dB
Sound power level LWA Uncertainty of measured value KWA	97 dB 3 dB
Sound peak value LpCpeak Uncertainty of measured value KpCpeak	99 dB 3 dB
Vibration value 1 αhv 3- way Vibration value 2 αhv 3-way	4,7 m/s²
Uncertainty of measured value $K\pmb{\alpha}$	1,5 m/s²

Application examples





Kompatibel mit AMPShare-/ Bosch Professional 18 V Akkus. | Compatible with AMPShare/Bosch

Professional 18 V batteries. | Compatible avec les batteries 18 V AMPShare/Bosch Professional. | Compatible con baterías AMPShare/Bosch Professional de 18 V. | Compatible con le batterie AMPShare / Bosch Professional da 18 V.







