



## BOP 10 set

### Hand Drill up to 10 mm

Compact single-speed drill with speed stability, up to 10 mm in steel for on-site installation work.

Product number: 7 205 53 61 00 0

## Details

- + Particularly flat and slim design with excellent width across corners for installation work even in tight spaces and corners.
- + FEIN high-power motor with good speed stability for constant drilling progress in almost any application.
- + Metal gear head and distortion-free barrel-type motor housing for superb service life.
- + Reversible.
- + High-precision metal drill chuck.
- + High concentricity.
- + Self-tightening drill chuck clamping jaws.
- + FEIN Sensitive Handle.
- + Variable speed control.
- + 5 metre cable.
- + 43 mm diameter collar for use in the drill jig.

## Price includes

- + 1 SUPRA SKE single sheath metal quick clamping drill chuck
- + 1 plastic carrying case
- + 1 additional handle

## Product feature

- + Reversible rotation
- + Acceleration electronics

## Application



Twist drilling

++

Tapping

++

Countersinking

+

+ suitable

++ well suitable

## Technical data

### TECHNICAL DATA

Input	500 W
Output	270 W
Speed, full load	0 - 900 rpm
Speed, no load	0 - 1,500 rpm
Torque at max. output power	9 Nm
Stall torque	24 Nm
Drill chuck clamping width	1.5 - 13 mm
Capacity in steel Ø	10 mm
capacity in Ø stainless steel	10 mm
Capacity in alu Ø	15 mm
Capacity in wood Ø	30 mm
Tapping	M 6
Thread of spindle	1/2"-20 UNF

### VIBRATION AND SOUND EMISSION VALUES

Sound pressure level LpA Uncertainty of measured value KpA	82 dB 3 dB
Sound power level LWA Uncertainty of measured value KWA	93 dB 3 dB
Sound peak value LpCpeak Uncertainty of measured value KpCpeak	96 dB 3 dB
Vibration value 1 $\alpha_{hv}$ 3-way Uncertainty of measured value K $\alpha$	$\alpha_{h,D}$ 3,0 m/s <sup>2</sup> 1,5 m/s <sup>2</sup>



**FEIN**

Collar Ø

43 mm

Width across corners

23 mm

Cable with plug

5 m

Weight according to  
EPTA

1.80 kg