

KFH 17-8 R

Beveller up to 8 mm

Universal beveller with booster technology for perfectly preparing welded seams and preparing subsequent coatings.

Product number: 7 238 16 61 00 0



Details

- + Milling performance improved by 30 - 80 % and vastly reduced vibrations thanks to new booster technology.
- + FEIN ErgoGrip: unique, ergonomic concept of two-handed operation for fatigue-free working (patent pending).
- + Efficient quick-change cutter system for minimal interruptions.
- + Effective material removal requiring little force.
- + Extensive user protection features include soft start, restart protection, jam monitoring and electronic overload protection.
- + Extensive range of accessories for various materials such as steel, stainless steel and non-ferrous metals.
- + Above-average service life of the indexable inserts due to 8-fold or 16-fold usability.

Price includes

- + 1 tool (without milling head, without guide roller, without indexable tips)
- + 1 x copper paste
- + 1 x TX 15 Torx screwdriver
- + 3 x clamping screws SX
- + 1 socket head wrench 5 mm
- + 1 plastic carrying case

Product feature

- + Soft start
- + Blockage monitoring
- + Speed preselection
- + Quick-change cutter system
- + Restart protection
- + Electronic overload protection
- + Booster technology

Application

Installation work





Bevel length of up to 5 mm at 45°

++

Bevel length of up to 8 mm at 45°

+

Workshop jobs

++

+ suitable

++ well suitable

Technical data

TECHNICAL DATA

Input	1,700 W
Output	1,000 W
Speed, no load	2,300 - 7,500 rpm
Max. bevel length at 45°	8 mm
Max. bevel height at 45°	5.7 mm
Bevel angle	30° / 37.5° / 45° / 60°
Radius	2 / 3 / 4 mm
Milling head configuration	3x KX tip
Support plate diameter	118 mm
Cable with plug	4 m
Weight according to EPTA	4.60 kg
Weight according to EPTA	4.60 kg

VIBRATION AND SOUND EMISSION VALUES

Sound pressure level LpA Uncertainty of measured value KpA	90 dB 3 dB
Sound power level LWA Uncertainty of measured value KWA	101 dB 3 dB
Sound peak value LpCpeak Uncertainty of measured value KpCpeak	104 dB 3 dB
Vibration value 1 α_{hv} 3-way Vibration value 2 α_{hv} 3-way	α_h , 5,4 m/s ² α_h , 6,2 m/s ²
Uncertainty of measured value K α	1,5 m/s ²

Application examples



 30° 6 43 01 002 01 0	 8 mm 0.315"	 2 mm 0.079"	 3 mm 0.118"	 4 mm 0.157"	 8 mm 0.315"	 2 mm 0.079"	 3 mm 0.118"	KX 10 x 3 13 90 075 00 0
 37.5° 6 43 01 005 01 0	 8 mm 0.315"	 2 mm 0.079"	 3 mm 0.118"	 4 mm 0.157"	 8 mm 0.315"	 2 mm 0.079"	 3 mm 0.118"	
 45° 6 43 01 001 01 0	 8 mm 0.315"	 2 mm 0.079"	 3 mm 0.118"	 4 mm 0.157"	 8 mm 0.315"	 2 mm 0.079"	 3 mm 0.118"	
 60° 6 43 01 007 01 0	 8 mm 0.315"	 2 mm 0.079"	 3 mm 0.118"	 4 mm 0.157"	 8 mm 0.315"	 2 mm 0.079"	 3 mm 0.118"	