United Kingdom



PRODUCT NUMBER: 3301161 Max (Uncorded)

Learn more about our products at howardleight.com

Learn more about hearing conservation at hearforever.org >



Overview

Reference Number 3301161

Product Type Hearing Protection

Range Earplugs

Line **Disposable Earplugs**

Brand

Howard Leight by Honeywell

Industry

- Industry
 Administration
 Agriculture
 Army Defence
 ATEX environment
- Automotive and Part Manufacturer
 Aviation
 Building and Construction
 Catering
- Chemical Industries
 Energy or Electricity
 Fire Protection brigades
 Fishing
 Food Industries
- Foundry
 Glass Industries
 Green Spaces
 Homeland defense
 Industrial Cleaning
- Iron and steel industry
 Laboratory
 Logistics
 Maintenance
 Medical and Pharmaceutical
 Metal steel
 Minning and Quarrying
 Offshore
 Paper Industries
 Petro-chemical
- Printing Industries
 Services
 Ship Building
 Telecoms
 Textile Industries
 Transportation
- Utilities
 Water treatment
 Welding
 Wood Industries

Product Use

Single-Use Earplug

Features & Benefits

Feature

POLYURETHANE FOAM Soft foam delivers superior long-wearing comfort and solid performance. BELL-SHAPED DESIGN Delivers maximum in-ear comfort without backing out of the ear canal, easier to insert. SMOOTH, SOIL-RESISTANT SKIN Prevents dirt or other substances from accumulating on earplug or entering ear canal.

Benefit

Workers who need to block out loud noise demand the best protection and comfort available in an earplug. That's where Max comes in. The world's most-used polyurethane earplug, Max offers superior noise-blocking performance in a single-use earplug. Max's new enhanced contoured shape is easier to insert and resists backing out of the ear canal,

> Page 1 Of 3 © Honeywell International Inc.

Max (Uncorded) - 3301161

while its softer foam delivers superior long-wearing comfort - delivering solid performance that your workers can depend on.

Technical Description

SNR (dB) 37 H (dB) 36 M (dB) 35 L (dB)

34

Attenuation Data

Frequency (Hz) Frequenz (Hz) Fréquence (Hz)	63	125	250	500	1000	2000	4000	8000
Mean Attenuation (dB) Mittlere Dämmung (dB) Atténuation moyenne (dB)	34.6	37.1	37.4	38.8	38.2	37.9	47.3	44.8
Standard Deviation (dB) Standardabweichung (dB) Déviation standard (dB)	3.0	4.5	4.3	3.7	3.5	4.0	3.5	7.2
Assumed Protection (dB) Angenommener (dB) Protection supposée (dB)	31.6	32.6	33.1	35.1	34.7	33.9	43.8	37.6

Size

Fits All

Color Orange

- ange

Shape bell

Corded

No

Weight (grs) 0.59

Certifications

E.C. Declaration of Conformity

EC Category PPE 2 Quality Assurance ISO 9001 / 2000

EC Certificate Number 1219

EC Attestation

EC Attestation Number 040366

User Manual

Instruction Manual - Max (global)

Maintenance

Life Cycle

These plugs must be disposed of and replaced after each wearing.

Storage Information

All earplugs should be stored before and between usages in a way that protects them from dirt, grease, and other contaminants.

Care Instructions

Disposable earplugs are made of either TPE (Thermoplastic elastomers) or polyurethane foam. Washing and cleaning of disposable earplugs are not recommended. These plugs must be disposed of and replaced after each wearing. Excessive moisture reduces the attenuation and slows down the foam recovery which may lead to improper fit.

Packaging

EAN Code 033552000037

© Honeywell International Inc.