

Purge Monitors

MasterPurge Pro2 mobile

The keypad is a very robust snap dome film. Stable plastic plates are installed between the polycarbonate and the conductor-film. This allows the operator a save pressure, also with heavy welders or working-gloves. By pressing the keys, he gets a not overhearing confirmation signal.

Furthermore a practicable software supports the operator with several information (5-fold signal tone before readiness to measure, signal tones as alert - no welding readiness).



Features:

- Temperature regulated zirconium sensor
- Graphics compatible display (4 background colours)
- Plug-in power supply 110 VAC-240 VAC
- Internal akku with 7 VDC, 2750 mAh
- Integrated, free programmable horn
- Easy operated software
- Operator guidance in several languages
- Diffusion-proof special- FPM- measuring hose
- Charging cable for car-cigarette lighter available
- Measuring-data storable (Premium version)
- PC software for documentation
- Various surfaces for documentation or connection of external orbital welding equipment (Orbitec, AMI, ...)



Graphics compatible display (4 background colours)

Technical Data:

Electrical voltage supply:	<ul style="list-style-type: none"> • Input: 100 – 240 VAC (50/60 Hz) • Output: 12 VDC, 1000 mA
Weight:	0,570g
Dimensions (L x W x H):	225mm x 105mm x 45mm
Range:	1000 - 5ppm